
7.0.2

- Added support for XPR5550 4-line display.
- Removed “Enlarge Text” client option since no longer needed because app is now resizable.

6.0.10

- Fixed DPI GUI issues.
- Crash Reporter fails to send data if OS or Serial number cannot be found.
- Solo failing to start on some XP machines.

6.0.9

- Added UIHandle.Invoke.
- Now using DirectX and NAudio for audio. (Not Alvas nor WinMM.)
- Re-made GUI.

6.0.1

- PTT button sticking with left-right mouse click combo.
- Hotkeys updated.
- Removed Gateway settings (Now only available through ICU).
- Removed Show Console.
- Setting Mic level causing PTT to delay, so changed to Async instead.

6.0.0

- ?

5.1.6

- Changed public demo address to new 198.144.49.99 address.
- Fixed graphic issues with texting window.

5.1.3 – 5.1.4

- Removed NAudio SaveWaveIn global lock, since it was causing delay in starting mic.
- Mini VU meter now uses same stream as client, and does not create second Wave In stream.
- Made TurboVUI Sound blocking event based instead on polling.
- Socket Connection clearing entire stream when de-serializing unknown ID.
- Intercom now works even when radio is disconnected.
- Added audio quality option; High Quality and Compressed.
- Changed Audio Output Processing:
 - i) Using buffer release callbacks instead of MMTimer syncing.
 - ii) Opening and Closing audio stream when not used, instead of Pausing/resuming.
 - iii) Delay time reduced when playing audio.
 - iv) Adding callbacks for when audio stream is done playing.
- Removed Alvas Audio completely and replaced with NAudio (File Streamer, File Writer)
- No more Auto Compress in Socket Connection.
- Recorder causing echo at end of transmission. Now checking Bytes Recorded property on Wave In.
- Removed Diagnostics window.

5.1.1

- Fixed locking problem if no mic is connected.

5.1.0

- Updated Delcom Dual Footswitch USB HID cfg because of falsing.
- Made all audio packet processing immediate, and not done using async.
- Used NAudio Save Wave In for Intel USB problem

5.0.11

- Gateway alias error if alias is removed. Annoying scrolling text eliminated.
- Flash texting window if new text is received and is hidden behind another window.
- Changed Auto Scale Mode to NONE. Fixes DPI problems on Win7.

5.0.10

- Effects volume not affecting sounds that loop.

5.0.9

- Handles new Notify Messages from server.
- Disconnects when trial is over and does not reconnect. Does not kill app any more.
- Added connection check timer.
- Handle error when mic level cannot be set before transmitting.

5.0.8

- Fixed Async Client; wasn't connecting properly, causing audio to echo back to PC.
- Changed Client audio settings to use Win MM Devices rather than Alvas.
- Added Buddy Mic USB Id 29205.

5.0.7

- No PC audio when cross mute is disabled.

5.0.6

- Clear browse history and active users after reconnect.
- Radio Enable/Disable/Remote Monitor for admin account only.
- Added Radio Check feature in Active Users.
- Added Call Alert feature in Active Users.
- Login Time in active users changed from universal time to local.
- Added cross muting.
- Active Users timeout option.
- Browse History was not showing any results in version 5.0.4.
- Text message window times were universal not local.
- TMS crash when sending/receiving text to user not in the user list.
- Changed TMS tooltip time from universal to local.

5.0.5

- Wait for PTT sound before transmitting.

5.0.4

- Use .NET Reactor 4.4.0.0 for obfuscation.
- Recent History and Browse History forms need local time instead of Universal.
- Added USB config for Delcom Dual Footswitch.
- Socket Client.Connect() failed if called repeatedly after connection.

5.0.3

- No Change

5.0.2

- Refer to TurboVUi Server 5.0.2 updates.

5.0.1

- Solo time is different than Dispatch time. (Was displaying UTC);
- Time settings are converted from UTC to local.
- Showed currently connected PC's in Active Users.
- "Enlarge display text option".
- "Clear texts after window closes" option.
- Replace ID's in display with aliases.
- Added mic VU meter.
- Persist mic level on transmit.
- Fixed display text bug when Ignoring font size from radio and resizing window.
- USB file is now "UsbHidDevices.cfgovr"
- Intercom is canceled if radio receives a call.

5.0.0

- Added additional debug audio logging.
- Updated usb hid config file.
- Set Turbovui_Gateway_Client.TransferTimeout from 2000 to 4000 for LTR mode.
- Fixed bug where error bonk didn't sound if radio dekeyed while user is transmitting.
- Slow connecting when DNS server not found.

4.0.3

- Change Password form not trimming password.

4.0.2

- Active Users Form making PC Slow.
- Tested 2000 radio aliases successfully.
- Fixed DPI auto scaling problem.

3.2.0

- Updated USB Config file with Buddy Mic 7G.
- Hide invisible channels/zones.

3.1.6

- Crashes with some windows 7 machines when calling HidP_GetButtonCaps().
- Active Users does not show any users.
- Reset 'last' timers on client when connecting to a Gateway.
- Changed default public demo gateway to 216.228.66.251 from 216.228.66.196

3.1.5

- Allowed All-Call group in gateway config.
- Allowed All-Call group in Client_User_Manageandr.ChangeUserStatus.
- Fixed effects-volume in client-settings.
- Removed Checkbox from GUI: Mute audio from PCs (Replaced by PC-Audio level Slide bar) .
- Error when re-writing a WAV effect while other instance is opened.